

HEAD FEED DR150A COMBINE HARVESTER

★ Use 75hp turbo engine with strong power and low fuel consumption.
★ The whole stem can be well kept after harvested by head feed combine harvester.
★ head feed combine harvester can harvest well with fallen crops.
★ automatic grain unloading and sack type grain unloading are optional.
★ Use big threshing cylinder to ensure low breakage and less loss.

Model		DR150A	DR150B
Dimension (Operation)	Length(mm)	4250	4250
	Width(mm)	2400	2400
	Height(mm)	2690	2690
Weight(kg)		2600	2600
Engine	Type	Vertical,water-cool,4-yllinder,direct injection,turbo charged	
	Power(HP)	52	52
	Rated Rotating Speed(r/min)	2700	2700
	Fuel Tank	90L	
Gear Box Model HST		Hydraulic Gear Box 40	
		30cc/37cc	
Chassis	Track(mm)	400×90×46	400×90×51
	Track Center(mm)	1000	1000
	Ground Clearance(mm)	Uses self-draining air filter	25
Header Platform	Cutting Width(mm)	1500	
	Row	4	
	Crop height(mm)	650-1300	
	Cutting Bar Lifting way	Hydraulic	
	Sleeping paddy adoptability	Reaping follow:≤85°;Reapin against:≤70°	
Thresher	Type	Low Threshing Axle Flow	
	Threshing Cylinder(mm)	Φ424×900	Φ424×900
	Rotating Speed(r/min)	510	510
Grain Tank	Separating Type	Vibrating Sieves + Centrifugal Fan	
	Big Grain Tank(0.7㎥)	Auto Gain Unloading(Vertical or 360degrees	
	Small Grain Tank(0.2㎥)	Sack	
Straw Unloading	Straw handling	Lay-flat/crush(50-60mm)	
	Blade tybe	Round bakle	Round bakle
	Work Efficiency(ha./h)	0.4-0.5	0.4-0.5
	Crops	Rice,Wheat	Rice,Wheat

FMWORLD

Wechat Public Number

Jiangsu World Agricultural Machinery Co.,Ltd.
Add: Picheng Idustrial Park,Danbei Town, Danyang City,Jiangsu
Postal Code:212311
Fax:+86-511-86349102
Tel:+86-511-86349102
Web:www.worldnyjx.com
Email:worldgroup@vip.163.com
Facebook:JIANGSUWORLD

FMWORLD
/ F O R T H E W O R L D /

COMMITTED TO
FULL MECHANIZATION
OF MODERN AGRICULTURE

CRAWLER TYPE
HARVESTER SERIES



RUILONG PLUS++ 4LZ–6.0P COMBINE HARVESTER



★ Use 102hp turbo engine with high power and low fuel consumption
★ Cutting Width 2.2m or 2.36m for different areas of fields.
★ Reel uses spring type finger and PVC bush for better performance.
★ WORLD special hydraulic gear box 85 with best quality.
★ Use 45cc HST for working smoothly.
★ Bigger threshing cylinder ensures grain lose less and much cleaner.
★ Grain tank capacity 1.6m3 or1.77m3 optional with 360 degree grain unloading,or sack type are optional.
★ Minimum ground clearance 360mm and rubber track 550*90*56 ensures machine work in deep mud field.
★ Comfortable Cabin with AC&Reverse images are optional.

RUILONG 4LZ–4.0E COMBINE HARVESTER



★ Use 88hp turbo engine with high power and low fuel consumption.
★ Basic cutting width 2.1m as standard,2m optional for smaller farmland.
★ Reel uses spring type finger and PVC bush for better performance.
★ WORLD special hydraulic gear box 85 with best quality.
★ Use 45CC HST for bigger hydraulic power.
★ Bigger threshing cylinder ensures grain less loss and much cleaner.
★ Big grain tank 1.4m³ with 360 degrees unloading and sack type are optional.
★ Rubber track 450*90*51 or 500*90*51 are optional.

RUILONG 4LZ–4.0E(SACK TYPE UNLOADING) COMBINE HARVESTER

★ Use 102hp or 88hp turbocharging Yuchai engine with lower diesle consuption and stronger power.
★ Two or three sack unloading joint are optional,meets for different need.
★ This model greatly saves grain unloading time and improves harvesting efficiency.
★ Equipped with 45CC HST and 85 gear box to ensure higher working speed.
★ lighter the whole machine can smoothly operate in mud field.
★ 500*51*90 or 550*56*90 two size rubber track can suit for different field condition.
★ Fuel tank capacity is 200L to meet one day's work.











Model		4LZ–4.0E	4LZ–6.0P
Type		Self-propelled Whole-feeding	Self-propelled Whole-feeding
Working Dimension	Length(mm)	4920	5150
	Width(mm)	2890	2620
	Height(mm)	2700	3030
Weight(Kg)		3200	
Engine	Type	Inline,Water-cooling,Four-stroke,Direct Injection	Inline,Water-cooling,Four-stroke,Direct Injection
	Power(hp)	88	102/110
	Rated Rotating Speed(r/min)	2600	2600
	Fuel Tank(L)	200	130
	Model	Changchai 4L88B/Xinchai 4D35ZT(I)17)	Changchai 4G33TC8/Yuchai YC4KD110
Gear Box Model		Hydraulic Type With HST	Hydraulic Type With HST
HST		45CC	45CC
Chassis	Track(mm)	450/500*90*51	550*90*56
	Track Center(mm)	1150	1350
	Ground Clearance(mm)	320	360
Header	Cutting Width(mm)	2100/2200	2200/2360
	Feeding Capacity(kg/s)	4.0	6.0
	Cutting Bar Lift	Hydraulic Control	Hydraulic Control
Thresher	Type	Axial Flow Type With Beat Bars	Axial Flow Type With Beat Bars
	Threshing Cylinder(mm)	Φ420*2010	Φ420*2010
	Separating Type	Vibrating Sieves + Centrifugal Fan	Vibrating Sieves + Centrifugal Fan
Grain Tank	Big Grain Tank(m³)	1.4m³, Auto Grain Unloading,Vertical Type	1.7m³, Auto Grain Unloading
	Small Grain Tank (0.25m³)	Sack	Sack
Working efficiency(ha/h)		0.37-0.66	0.5-0.9
Crops		Rice,Wheat,Soybean,Rapeseed	Rice,Wheat,Soybean,Rapeseed

